



DEPARTMENT OF CIVIL AVIATION
Private Bag 322, Lilongwe 3
Tel: (265) 01770577
Facsimile: (265) 01774986
E-mail: aviationhq@malawi.net

No.: A20
Issue: 2
Date: August, 1986

DCA (AIRCRAFT) NOTICE

MICROBIOLOGICAL CONTAMINATION OF FUEL TANKS OF TURBINE ENGINE AIRCRAFT

1. Introduction

- 1.1 Reports have been received that aircraft regularly operating in climate conditions such as those prevailing between the latitudes 30 degrees North and 30 degrees South have been contaminated in the fuel tanks by a fungus. Another aircraft regularly operating from the United Kingdom was found to have localized area of heavy growth when inspected after standing in a heated hangar for two months with fuel in the tanks. It is considered that the storage conditions were contributory factor.
- 1.2 In one case contamination was found during an investigation into the cause of erratic fuel contents indication, when white crusty deposits and brown stains were seen on the probes. Further examination revealed the presence of brown/black slimes adhering to horizontal upwards facing surfaces within the tanks. Examination by the Commonwealth Mycological Institute, Kew, confirmed that this substance was a fungal growth of the type *Cladesporium Resinae*.

2. Effects of Contamination

- 2.1 The problems associated with microbiological growths have been known for some years and research into their behaviour has been conducted throughout the world. In the case of *Cladesporium Resinae*, the spores of the fungus can exist in a dormant state in Kerosene fuels in most parts of the world. These will only develop when in contact with water in fuel at temperatures such as those reached when the aircraft or storage tanks are exposed to a warm ambient temperature such as radiation from the sun for long periods in tropical or sub-tropical environment, or prolonged periods in heated hangar.

- 2.2 Where fungus has formed there is a probability that corrosion will occur, Corrosion has been found where fungus had formed on the bottom tank skin, on the chordal support members in the wing root and on fuel pipes within the tank. In some cases aircraft have been sufficiently affected to necessitate replacement of some component parts.
- 2.3 The fungus itself, if dislodged by fuel during refueling can obstruct fuel filters.

3. Inspection

- 3.1 Operators uplifting fuel or operating regularly in areas having high normal ambient temperatures and high humidity or where fungus development is known to have been encountered, are advised to scrutinize tank areas for signs of fungus whenever access is gained for any purpose. It is further recommended that, for aircraft operating under these conditions, maintenance schedules should be amended to include a visual internal tank check at periods prescribed by the aircraft constructor. It is also important, whenever fuel tanks are inspected, to ensure that all passage ways between rib cleats etc, are not obstructed, so that a drainage path for water is maintained at all times. If the aircraft has been standing in a heated hangar for prolonged periods the fuel tanks should be treated with a biocide (see paragraph 4).
- 3.2 If contents gauges give suspect indications, immediate consideration should be given to the possibility that tank probes may be contaminated with water and/or fungus and appropriate inspections should be carried out.
- 3.3 Whenever fuel filters are checked they should be closely examined for the presence of slimes of any colour.
- 3.4 The need to prevent water collection by good maintenance practices and control of fuel supplies is emphasized. A high degree of protection can be maintained by strict adherence to water drain checks before and after refueling and, if the aircraft has been standing for any length of time, again before the next flight. Fuel quality control checks should be rigorously applied.

4. Treatment

- 4.1 If fungus is discovered, the fuel tank should be cleaned as soon as possible by a method approved by the aircraft constructor and the engine manufacturer. It must be appreciated that if the fungus is allowed to develop, cleansing and rectification could become a major operation involving grounding of the aircraft for a long period.
- 4.2 It is strongly recommended that when aircraft operate in an area where fungal growth can be encountered, or where there is any possibility of temperatures in the fuel tanks frequently rising above 25 C. a fungicide additive should be used in the fuel as approved by the aircraft constructor and the engine manufacturer. The frequency of treatment and the dilutions prescribed by the aircraft constructor and the engine manufacturer must be adhered to. Introduction of an unapproved fungicide or inhibitor may jeopardize the safe operation of the aircraft.

Cancellation:

This Notice cancels DCA Notice to Aircraft Owners and Aircraft maintenance Engineers No. A20 Issue1.

J.L Kalemera
CHIEF CIVIL AVIATION OFFICER